

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client : HTT Floorin 16/42-44 Bin Lidcombe N	nie Avenue		Test Numbe Issue Date Print Date	r : : :	19-00257 11/07/201 11/07/201	9	
Sample Description	Clients Ref : "Quercus" Engineered Timber flooring Colour : Natural End Use : Flooring Nominal Composition : Timber Nominal Mass per Unit Area/Density : Nominal Thickness : 15mm	2.24kg/m2	2				
'ISO 9239.1-2003	Reaction to Fire Tests for Floorings. Radiant Heat Source	Determination	of the Burning B	ehavi	our using a		
	Date of Sample Arrival		15/05/2019				
	Date Tested	ate Tested 10/07/2019					
	CHF Value	1	2	3	Mean		
	Length	5.4	-	-	-	kW/m²	
	Width	3.0	3.4 3	.4	3.3	kW/m²	
	HF-30 Value	1	2	3	Mean		
	Length	-	-	-	-	kW/m²	
	Width	3.1	- 3	.8	-	kW/m²	
	Smoke Value	1	2	3	Mean		
	Length	19	-	-	-	%.min	
	Width	6	16	12	11	%.min	
	Blistering				Yes		
	Penetration of flame through to substra	ate			Yes		

172241

36041

© Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing : Accred - Mechanical Testing : Accred - Performance & Approvals Testing : Accred

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No. : Accreditation No. : Accreditation No. 983 985

1356

Page 1 of 2



APPROVED SIGNATORY

0204/11/06



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client : HTT Flooring 16/42-44 Birnie Avenue Lidcombe NSW 2141

Test Number	:	19-002578
Issue Date	:	11/07/2019
Print Date	:	11/07/2019

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was clamped to a substrate of 6mm thick fibre reinforced cement board prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

HF30 not reported as flame out time occurred before 30 minutes.

172241 Australian Wool testing Authority Ltd Copyright - All Rights Reserved

36041



the Managing Director of AWTA Ltd.

Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

: Accreditation No. : Accreditation No. : Accreditation No.

No. 9 No. 9 No. 13

983 985 1356

Page 2 of 2

AWTA LIMITED





APPROVED SIGNATORY

0204/11/06

C